

Ordering Code for Control Head Cables

2 1 L 3 2 DF (6) - 3 - 120 /

Control Head Type -----

- 2 Micro Adjust
- 5 Twist Lock with 2.38" Plastic Handle
- 6 Twist Lock 3.5" Metal Handle
- 7 Non-Locking with 3.8"-24 UNF Mounting
- 8 Non-Locking with 7/16"-20 UNF Mounting
- 9 Non-Locking with 5/8"-18 UNF Mounting

Cable Type -----

- 1 Low Friction - EXT
- 6 Utility

Cable Size -----

- V Very Light Duty
- L Light Duty

Stainless Steel Options -----

- 0 Carbon Steel Fittings
- 3 With Stainless Steel End Rod
- 4 With Stainless Steel End Rod, Support Tube, and Innermember Armor

Output End Fittings -----

- 2 Threaded Swivel
- 3 Grooved Swivel

Micro Adjust only Cable Options -----

- D Disconnect Feature
- F Friction Lock Accessory

Seal Options (Use This Number only if Requesting Optional Seals) -----

- 5 Improved Model 5 Wiper Seal Is Standard on Low Friction - EXT and Utility
- 6 Model 6 wiper Seal, Optional on All Controls

Cable Travel - 1" To 3" -----

(For Output Fittings Style 2 and 3 Only)

Overall Length -----

See Overall Length Dimensions Points Indicated on Each Illustration

Knob Option (For Control Head Types 7, 8, And 9) -----

See Page 9 Handle Options