

Ordering Code for Push-Pull Cable Controls

314 (6) - L TT - 3 - 144 (AP)

Control Type -----

Low Friction - EXT

313 With Stainless Steel End Rods

314 With Stainless Steel Support Tubes, and End Rods

315 All Exposed Fittings/parts are Stainless Steel

Utility

173 With Stainless Steel End Rods

174 With Stainless Steel Support Tubes, End Rods and
Innmember Armor

175 All Exposed Fittings/parts are Stainless Steel Plus
Stainless Innmember Armor

Seal Options -----

(Use This Number Only If Requesting Optional Seals)

6 Model 6 Wiper Seal, Optional on all Controls

Cable Size -----

Letter	End Rod Thread	Letter	End Rod Thread
V	10-32 UNF	L	1/4-28 UNF
M	5/16 UNF	H	3/8 UNF

End Fitting Combination -----

T Threaded Swivel

G Threaded Swivel

Cable Travel, In Inches (1", 2", 3", 4", 5", 6") -----

Length, In Inches +/- .25 Inches -----

Suffix Letters For Additional Features -----

(Use Only If Requesting Optional Features)

N End Rod Jam Nuts (2 each)

A Combination of N and W

S Stamp with Cablecraft and
Customer Part Number

W Extra Shakeproof Washers on Conduit Ends

P Stamp with Customer Part Number

M Metric End Rods (Optional)

V M5 x .8

L M6 x 1.0

M M8 x 1.25

H M10 x 1.5